



TECHNICAL DATA:

- Welded nut M8/M10 for all sizes
- Electro-galvanized
- M6 side screws
- Breaking load in traction: 6000 N
- Safe working load: 2000N
- Can be used for both horizontal and vertical installations

Reference	mm	inches	Dimensions (mm)				Width x thickness (mm)
	D	D	B	b1	H1	H	
RSC 018	15-19	3/8"	54	20	43	29	20 x 2.0
RSC 022	20-25	1/2"	59	20	49	32	20 x 2.0
RSC 028	26-30	3/4"	66	20	55	35	20 x 2.0
RSC 035	32-36	1"	73	20	62	38	20 x 2.0
RSC 040	38-45	1 1/4"	82	20	71	43	20 x 2.0
RSC 048	47-51	1 1/2"	89	20	79	47	20 x 2.0
RSC 054	53-56	-	93	20	84	50	20 x 2.0
RSC 060	60-64	2"	100	20	89	52	20 x 2.0
RSC 070	68-72	-	112	20	98	57	20 x 2.0
RSC 075	74-80	2 1/2"	126	20	111	63	20 x 2.0
RSC 083	81-86	-	126	20	112	63	20 x 2.0
RSC 090	87-92	3"	130	20	112	64	20 x 2.0
RSC 100	99-105	3 1/2"	138	20	120	68	20 X 2.0
RSC 110	107-112	-	146	20	129	72	20 x 2.0
RSC 115	113-118	4"	157	20	137	76	20 x 2.0
RSC 125	125-130	-	166	20	145	80	20 x 2.5
RSC 133	131-137	-	168	20	147	81	20 x 2.5
RSC 140	138-142	5"	176	20	159	87	20 x 2.5
RSC 150	148-152	-	188	20	167	91	20 X 2.5
RSC 160	159-166	6"	195	20	175	95	20 x 2.5
RSC 168	168-172	-	218	20	197	106	20 x 2.5
RSC 200	200-212	-	220	20	199	107	20 x 2.5
RSC 220	215-220	8"	300	20	257	137	20 x 2.5