


TECHNICAL DATA:

- Welded nut M8/M10 for all sizes
- Electro-galvanized
- M6 side screws
- Breaking load in traction: 6000 N
- Safe working load: 2000N
- EPDM sound insulation lining

Reference	mm	inches	B	Dimensions (mm)		H	Width x thickness (mm)
	D	D		b1	H1		
RRLSC 018	15-19	3/8"	54	20	43	29	20 x 2.0
RRLSC 022	20-25	1/2"	59	20	49	32	20 x 2.0
RRLSC 028	26-30	3/4"	66	20	55	35	20 x 2.0
RRLSC 035	32-36	1"	73	20	62	38	20 x 2.0
RRLSC 040	38-43	1 1/4"	82	20	71	43	20 x 2.0
RRLSC 048	47-51	1 1/2"	89	20	79	47	20 x 2.0
RRLSC 054	53-58	-	93	20	84	50	20 x 2.0
RRLSC 060	60-64	2"	100	20	89	52	20 x 2.0
RRLSC 070	68-72	-	112	20	98	57	20 x 2.0
RRLSC 075	74-80	2 1/2"	126	20	111	63	20 x 2.0
RRLSC 083	81-86	-	126	20	111	63	20 x 2.0
RRLSC 090	87-92	3"	130	20	112	64	20 x 2.0
RRLSC 100	99-105	3 1/2"	138	20	120	68	20 x 2.0
RRLSC 110	107-112	-	146	20	129	72	20 x 2.0
RRLSC 115	113-118	4"	157	20	137	76	20 x 2.0
RRLSC 125	125-130	-	166	20	145	80	20 x 2.5
RRLSC 133	131-137	-	168	20	147	81	20 x 2.5
RRLSC 140	138-142	5"	160	20	151	83	20 x 2.5
RRLSC 150	148-152	-	176	20	159	87	20 x 2.5
RRLSC 160	159-166	6"	188	25	167	91	25 x 2.5
RRLSC 168	168-172	-	195	25	175	95	25 x 2.5
RRLSC 200	200-212	-	218	25	197	106	25 x 2.5
RRLSC 220	215-220	8"	220	25	199	107	25 x 2.5